

Peeltex Vert

GENERAL CHARACTERISTICS

The Peeltex Vert is a peel ply in Nylon (Polyamide fibers PA66)

The Peeltex Vert is used during the implementation of the vacuum process (infusion, pre preg)

It can also be used on Hand lay up

The Peeltex Vert holds to temperature up to 180°C

Use :

- Allow to separate the contact molding from the vacuum fabrics in order to "peel them off" after polimerization
- Obtaining a very good quality surface
- Protection of the "pieces" against surface contamination (dust, grease...)

APPLICATION

The Peeltex is placed on a dry contact surface (infusion, pre preg) or a moist stratification, in excess by few centimeters (flow of resin)

Above you will place the other materials for the vacuum system (Perforex, Bleedex, Nylex...)

In case of use on wet process, it will be placed on the stratification still being moist

CARACTERISTIQUES TECHNIQUES

Couleur / Color	Vert Fluo / Fluo Green
Grammage / Nominal Weight	83 g/m ² ±3%
Armure / Weaving style	Taffetas/ Plain
Type de fibre / Fiber Type	Nylon PA 66
Résistance à la traction / Tensile Strength	
Chaine / Warp	> 320 N/cm
Trame / Weft	> 255 N/cm
Tenue en Température / Temperature resistant	180° C ± 0.5

LEGAL NOTES: SICOMIN reserves the right to change the properties of its products. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data and tolerance may vary due to circumstances beyond our control. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

MENTIONS LÉGALES : SICOMIN se réserve le droit de modifier les propriétés du produit. Toutes les caractéristiques spécifiées dans cette Fiche technique sont basées sur des tests de laboratoire. Les mesures et leurs tolérances effectives peuvent varier pour différentes raisons. SICOMIN ne donne aucune garantie de quelque nature que ce soit si ce n'est que les matériaux fournis sont de qualité standard. Tous les risques et responsabilités découlant de la manutention, le stockage et l'utilisation des produits, ainsi que le respect des restrictions légales applicables, incombe à l'utilisateur.