

Sealtex S2

Description

The SEALTEX S2 is a rubber sealing tape with a high stickiness and a permanent plasticity. For ease of use, this pre formed vacuum tape is available in rolls. SEALTEX S2 is essential to create a good seal during the vacuum process (vacuum laminating, infusion, compaction of the pre-pregs, core laminating....)

The SEALTEX S2 is compatible with the vast majority of vacuum films

Surface preparation

All contact surfaces need to be clean and dry and with no grease marks.

On waxed surfaces, make sure it's clean dry.

Application

Thanks to its roll packaging, the SEALTEX S2 is used as a conventional tape. When placing it on support, leave the protective film on. That film will be removed as you place the vacuum film, this will make the process easier and will allow it to remain tacky (surface contamination due to the environment/workshop)

Caution

To have an effective seal, you must ensure the SEALTEX S2 is well placed on the support and on the vacuum film, and well stuck

Technical Characteristics

Color: light grey

Dry extract: 100 %

Temperature: +10°C to +35°C.

Temperature resistance: + 23°C to + 90 °C maximum

Packaging

Dimensions: 10mm x 3 mm.

Roll length: 13 m.

Box of 22 rolls.

Stockage

Please keep away from frost, in a well ventilated area at a maximum temperature of 30°C

LEGAL NOTES: SICOMIN reserves the right to change the properties of its products. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data and tolerance may vary due to circumstances beyond our control. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

MENTIONS LÉGALES : SICOMIN se réserve le droit de modifier les propriétés du produit. Toutes les caractéristiques spécifiées dans cette Fiche technique sont basées sur des tests de laboratoire. Les mesures et leurs tolérances effectives peuvent varier pour différentes raisons. SICOMIN ne donne aucune garantie de quelque nature que ce soit si ce n'est que les matériaux fournis sont de qualité standard. Tous les risques et responsabilités découlant de la manutention, le stockage et l'utilisation des produits, ainsi que le respect des restrictions légales applicables, incombe à l'utilisateur.